


DM100E Series

UltraMiniature, 1W SIP Single & Dual Output DC/DC Converters



Key Features:

- 1W Output Power
- UltraMiniature SIP Case
- Low 0.3 Inch Profile
- Single & Dual Outputs
- 1,000 VDC Isolation
- >3.5 MHour MTBF
- 12 Standard Models
- **LOWEST COST!!**



MicroPower Direct

292 Page Street
Suite D
Stoughton, MA 02072
USA

T: (781) 344-8226

F: (781) 344-8481

E: sales@micropowerdirect.com

W: www.micropowerdirect.com



Electrical Specifications

Specifications typical @ +25°C, nominal input voltage & rated output current, unless otherwise noted. Specifications subject to change without notice.

Input

Parameter	Conditions	Min.	Typ.	Max.	Units
Input Voltage Range	5 VDC Input	4.5	5.0	5.5	VDC
	12 VDC Input	10.8	12.0	13.2	
Input Filter	Internal Capacitor				
Reverse Polarity Input Current				0.3	A

Output

Parameter	Conditions	Min.	Typ.	Max.	Units
Output Voltage Accuracy			±1.0	±3.0	%
Output Voltage Balance	Dual Output , Balanced Loads		±0.1	±1.0	%
Line Regulation	For Vin Change of 1%		±1.2		%
Load Regulation, See Note 1	See Model Selection Guide				
Ripple & Noise (20 MHz)	See Note 2		50	75	mV P - P
Output Power Protection		120			%
Temperature Coefficient			±0.02	±0.03	%/°C
Output Short Circuit	Momentary (1.0 Sec.)				

General

Parameter	Conditions	Min.	Typ.	Max.	Units
Isolation Voltage	60 Seconds	1,000			VDC
Isolation Resistance	500 VDC	1,000			MΩ
Isolation Capacitance	100 kHz, 1V		60		pF
Switching Frequency			100		kHz

Environmental

Parameter	Conditions	Min.	Typ.	Max.	Units
Operating Temperature Range	Ambient	-40	+25	+85	°C
Operating Temperature Range	Case	-40		+90	°C
Storage Temperature Range		-55		+125	°C
Cooling	Free Air Convection				
Humidity	RH, Non-condensing			95	%

Physical

Case Size	0.65 x 0.23 x 0.30 Inches (16.5 x 5.9 x 7.5 mm)				
Case Material	Non-Conductive Black Plastic (UL94-V0)				
Weight	0.07 Oz (2.1g)				

Reliability Specifications

Parameter	Conditions	Min.	Typ.	Max.	Units
MTBF	MIL HDBK 217F, 25°C, Gnd Benign	3.5			MHours

Absolute Maximum Ratings

Parameter	Conditions	Min.	Typ.	Max.	Units
Input Voltage Surge (1 Sec)	5 VDC Input	-0.7		9.0	VDC
	12 VDC Input	-0.7		18.0	
Lead Temperature	1.5 mm From Case For 10 Sec			300	°C
Internal Power Dissipation	All Models			450	mW

Caution: Exceeding Absolute Maximum Ratings may damage the module. These are not continuous operating ratings.

www.micropowerdirect.com

Model Number	Input				Output			Load Regulation (% Max)	Efficiency (% Typ)	Fuse Rating Slow-Blow (mA)
	Voltage (VDC)		Current (mA)		Voltage (VDC)	Current (mA, Max)	Current (mA, Min)			
	Nominal	Range	Full-Load	No-Load						
DM101E	5	4.5 - 5.5	273	30	5.0	200.0	20.0	15	73	500
DM102E	5	4.5 - 5.5	270	30	12.0	83.0	9.0	15	74	500
DM103E	5	4.5 - 5.5	263	30	15.0	67.0	7.0	15	76	500
DM104E	5	4.5 - 5.5	278	30	±5.0	±100.0	±10.0	15	72	500
DM105E	5	4.5 - 5.5	256	30	±12.0	±42.0	±5.0	15	78	500
DM106E	5	4.5 - 5.5	256	30	±15.0	±33.0	±4.0	15	78	500
DM111E	12	10.8 - 13.2	107	15	5.0	200.0	20.0	15	78	200
DM112E	12	10.8 - 13.2	103	15	12.0	83.0	9.0	15	81	200
DM113E	12	10.8 - 13.2	105	15	15.0	67.0	7.0	15	79	200
DM114E	12	10.8 - 13.2	114	15	±5.0	±100.0	±10.0	15	73	200
DM115E	12	10.8 - 13.2	105	15	±12.0	±42.0	±5.0	15	79	200
DM116E	12	10.8 - 13.2	105	15	±15.0	±33.0	±4.0	15	79	200


Notes:

- Output load regulation is specified for a load change of 10% to 100%.
- These units should not be operated with a load under 10% of full load. Operation at no-load may cause damage to the unit.
- These converters will operate without external components. However, when measuring output ripple, it is recommended that an external ceramic capacitor be placed from the +Vout pin to the -Vout pin for single output units and from each output to common for dual output units. An input capacitor will enhance stability over temperature and input line variations. Recommended capacitor values are given in the table above. For applications requiring very low output noise levels, a simple LC filter should be effective.

Vin	Input Capacitor	Vout	Output Capacitor	
			Single	Dual
5 VDC	4.7 μF	5 VDC	10.0 μF	4.7 μF
12 VDC	2.2 μF	12 VDC	2.2 μF	1.0 μF
		15 VDC	1.0 μF	0.47 μF

- Dual output units may be connected to provide a 10V, 24V or 30 VDC output. To do this, connect the load across the positive (+Vout) and negative (-Vout) outputs and float the output common
- It is recommended that a fuse be used on the input of a power supply for protection. See the Model Selection table above for the correct rating.

Derating Curve




Pin Connections

Pin	Single	Dual	Pin	Single	Dual
1	+Vin	+Vin	5	No Pin	Common
2	-Vin	-Vin	6	+Vout	+Vout
4	-Vout	-Vout			

Notes:

- All dimensions are typical in inches (mm)
- Tolerance x.xx = ±0.01 (±0.25)
- Pin 1 is marked by a "dot" or indentation on the side of the unit

Mechanical Dimensions



MicroPower Direct
 We Power Your Success - For Less!