MPE-350CMU

350W, High Isolation AC/DC Power Supplies



Key Features:

- 350W Output Power
- 85-305 VAC Input
- 4,000 VAC Isolation
- Efficiency to 94%
- -40°C to +85°C Temp
- Meets EN 55032 B
- >300 kHour MBTF
- 150% Pk Load for 1 Sec
- Reinforced Insulation

Electrical Specifications

Specifications typical @ +25°C, nominal input voltage & rated output current, unless otherwise noted. Specifications subject to change without notice.

Input

Parameter	Conditions		Min.	Typ.	Max.	Units
Input Voltage Range	Rated Input (Certified Voltage)		100		277	VAC
	AC Input		85		305	
	DC Input		120		430	VDC
Input Frequency			47		63	Hz
Input Current	115 VAC				4	A
	230 VAC				2	
Inrush Current (Cold Start)	115 VAC			16.7		A
	230 VAC			42.3		
Power Factor	Full Load	115/230 VAC	0.98			
Leakage Current	240 VAC				0.5	mA

Output

Parameter	Conditions			Min.	Typ.	Max.	Units
Output Voltage Accuracy	Full Load	5V Output			±2		%
		Other Outputs			±1		
Line Regulation	Rated Load	5V Output			±0.5		%
		Other Outputs			±0.3		
Load Regulation	0-100% Load	5V Output			±1		%
		Other Outputs			±0.5		
Ripple & Noise (20 MHz)	5, 12V Outputs					200	mV P - P
	Other Outputs					240	
Hold-Up Time	115/230 VAC			12			ms
Temperature Derating	With Heat-Sink Plate		+55 to 85°C	2.33			%/°C
	110VAC, No Heat-Sink Plate		+55 to +85°C	1.33			
	230 VAC, No Heat-Sink Plate	5V	+55 to +70°C	2			
			+70 to +85°C	1.33			
		Others	+55 to +70°C	3.33			
			+70 to +85°C	1.33			
Input Voltage Derating	85 - 100 VAC			2			%/VAC
Over Temperature Protection	Output voltage turn off, self-recovery						
Over Load Protection	Room/high temperature			110		200	%Io
	Low temperature			110			
Short Circuit Protection	Recovery time <5s after short circuit removed			Continuous, Self-Recovery			

General

Parameter	Conditions	Min.	Typ.	Max.	Units
Isolation Voltage	Input - Output	4000			VAC
	Input - Ground	2000			
	Output - Ground	1500			
Isolation Resistance	See Note 8	50			MΩ

Environmental

Parameter	Conditions	Min.	Typ.	Max.	Units
Operating Temperature Range	Ambient	-40		+85	°C
Storage Temperature Range		-40		+85	°C
Operating Humidity	Non-condensing	20		90	%RH
Storage Humidity		10		95	

Physical

Size	8.66 x 2.44 x 1.22 in. (See Mechanical Drawing on Page 4)
Case Material	Metal (AL6063, SGCC)
Weight	23.99 oz (680g) (See Mechanical Drawing on Page 4)

Environmental

Parameter	Conditions	Min.	Typ.	Max.	Units
MTBF	MIL HDBK 217F, 25°C, Gnd Benign	300			kHours
Safety Standards	See Model Selection Guide				
Safety Class	Class I				

MicroPower Direct
46 Eastman Street
Unit 1
Easton, MA 02375
USA

T: (781) 344-8226
F: (781) 344-8481
E: sales@micropowerdirect.com
W: www.micropowerdirect.com

MICROPOWER DIRECT

Model Selection Guide

UL	Model Number	Input		Output			Over Voltage Protection (VDC) See Note 5	Output Capacitive Load (μF Max)	Efficiency (%, Typ)
		Current (A)		Voltage (VDC)	Current (A, Max)	Power (W)			
		115 VAC	230 VAC						
	MPE-350CMU-05	4	2	5	60	300	6.5	6000	90
▪	MPE-350CMU-12	4	2	12	29.2	350.4	15.6	4000	92
▪	MPE-350CMU-24	4	2	24	14.6	350.4	31.2	3000	94
▪	MPE-350CMU-28	4	2	28	12.5	350	35.0	2500	94
	MPE-350CMU-36	4	2	36	9.75	351	46.8	2000	94
▪	MPE-350CMU-48	4	2	48	7.32	350.4	62.4	1000	94
	MPE-350CMU-54	4	2	54	6.48	349.92	63.0	800	94
	* MPE-350CMU-12, -24, -28, -48 have UL/cUL 62368 recognition (UL certificate). Contact factory for safety standard status of other models.								

Notes:

1. The “tip and barrel method” is used for ripple and noise test, output parallel 10uF electrolytic capacitor and 1uF ceramic capacitor.
2. EMC performance indicators are on page 6.
3. Output short circuit protection is provided by a "hiccup mode" circuit. The unit recovers automatically when the fault condition is removed.
4. Input-output isolation is tested for 60 seconds with a leakage current of <5 mA.
5. A temperature derating of 5°C/1000m is required for operating altitude greater than 2000m.
6. The output voltage can be adjusted by the ADJ knob. Turn clockwise to increase and counterclockwise to decrease.
7. At light load an audible noise is generated in order to improve efficiency. This does not affect performance or reliability.
8. Isolation resistance is given for input - output, input - ground and output - ground. It is tested at 500VDC.

For the protective terminal cover option, add the suffix "**-TC**" to the model number (i.e. **MPE-350CMU-12-TC**).

Temperature Derating with Heat Sink



Temperature Derating: No Heat Sink



Input Voltage Derating (+25°C)



Case Temperature Derating



Efficiency vs Input Voltage: 5V (Full Load)



Efficiency vs Output Load: 5V (230VAC)



Efficiency vs Input Voltage: 12V (Full Load)



Efficiency vs Output Load: 12V (230VAC)



Efficiency vs Input Voltage: 48V (Full Load)



Efficiency vs Output Load: 48V (230VAC)



EMI Characteristics

Parameter	Standard	Criteria	Level
Radiated Emissions (RE)	CISPR32/EN55032		B
Conducted Emissions (CE)	CISPR32/EN55032		B
Harmonic Current	IEC/EN61000-3-2		A
Voltage Flicker	IEC/EN61000-3-3		
ESD	IEC/EN61000-4-2	A	Contact ±6KV/Air ±8KV
RS	IEC/EN61000-4-3	A	10V/m
EFT	IEC/EN61000-4-4	A	±2KV
Surge	IEC/EN61000-4-5	A	line to line ±2KV/line to ground ±4KV
CS	IEC/EN61000-4-6	A	10 Vr.m.s
Voltage Dips, Short, Interruption	IEC/EN61000-4-11	B	0%, 70%

Mechanical Diagrams





Pin-Out	
Pin	**Function**
1	GRND
2	AC(N)
3	AC(L)
4	+Vo
5	+Vo
6	-Vo
7	-Vo

Notes:
- All dimensions are typical in inches (mm)
- ADJ: Output voltage adjustable
- General tolerances: ±0.039 (±1.00)

Weight:
- 23.99 oz (680g)

Connector Wires Range			
Model	**Input Connector**	**Output Connector**	**Output Connector (Double Wires)**
5V	22-14AWG	12AWG	-Vo double wires
12V		16-12AWG	
Others		18-12AWG	+Vo double wires
Screw/Torque	M3.0, Max 0.5N · m	M3.5, Max 0.8N · m	

Installation Diagram





Position	Screw Spec	Torque (max)
1 - 4	M3	0.4N · m

Notes:

1. In order to meet the derating curve, the product must be installed onto an aluminum plate heat sink. The size of the suggested aluminum plate is shown above. To optimize thermal performance, it is necessary to apply thermal grease on the bottom of the product.
2. It is suggested to install the produxt with M3 combination screws, and the product must be firmly installed at the center of the aluminum plate.